

TITLE OF THE INVENTION

IMAGE DISPLAY APPARATUS AND METHOD, AND STORAGE MEDIUM

5

BACKGROUND OF THE INVENTION

## Field of the Invention

The present invention relates to an image display apparatus and image display method for displaying two  
10 images of the same subject obtained, for example, at different times, and a storage medium storing a program for implementing the image display method.

## Prior Art

15 Medical X-ray images, in particular X-ray images of the human chest, are indispensable to medical diagnosis, and are very widely used even today.

Chest X-ray images are used for examining the extent of progress of a disease or for examining for  
20 changes indicative of outbreak of a disease in a patient who is the subject of the X-ray radiography. Such examinations are often carried out by comparing current and past X-ray images of the same patient. In  
25 such a comparison, the past image and the current image are generally displayed simultaneously or films thereof are presented simultaneously, and an observer looks for differences between the two.

09923199-080601

Moreover, as described in "Application of digital image change detection to diagnosis and follow-up of cancer involving the lungs; Kinsey, J.H. and Vannelli, B.D.; SPIE70: 99-112; 1975", attempts are being made to develop a method in which a differential image between a past image and a current image is generated and this differential image is viewed, thus allowing the differences between the past image and the current image to be seen clearly. Research into making this method fit for practical use is still in progress.

A specific problem being researched is how to cope with changes in the radiographic conditions between the past image and the current image. In particular, the positional relationship between the X-ray source, the radiographic subject and the image receiving section may vary greatly due to differences in the radiographic environment and the radiographer between the past radiography session and the current radiography session.

As a result, the straightforward difference between the past image and the current image may indicate changes in the position from which the X-ray was taken rather than changes in the lung field as intended. A technique commonly used at present is called "image warping", which involves paying attention to the shape of the ribs in particular in the past image or the current image and warping the image, thus allowing the difference between the two images to be

09923199-080601  
T09080-661E2660

5 MacMahon, H.M., Xu X-W., et al.; Radiology 202: 447-452; 1997").

Moreover, from the standpoint that eliminating the shadow of the ribs is different to observing changes in the shadow of the lung field, which is the original objective, an alternative method has been devised in which attention is not paid to the ribs, but rather only the lung markings are extracted from the images and the difference between the images is obtained by aligning the lung markings (see "Hai-monri o taishou to shita gazou-ichi-awase-hou - Kyoubu X-sen gazou no jikanteki-sabun-hou (Image alignment method targeting lung markings - Temporal difference method for chest X-ray images); Sanada et al.; Japanese Journal of Radiological Technology; Vol. 56, No. 3, 398-404; 2000").

However, the radiographic subject is generally 3-dimensional having depth, but the radiographed image is only a 2-dimensional projection of the radiographic subject. Regardless of how this projected image which gives only 2-dimensional information is changed through warping, it is thus fundamentally impossible to obtain the difference between two images in 3 dimensions.

5

10

15

In a preferred embodiment of the present invention,  
the image display apparatus comprises position

designated position on the display screen of the display means in accordance with operational input from the observer, and the display control means is responsive to a position being designated by the position designation means, for controlling the display means to display a mark in the designated position on the display screen of the display means in a manner being superposed on each of the two images.

10        Preferably, each of the two images is an image produced from a radiation intensity distribution.

Also preferably, the two images are a past image and a current image taken of the same human subject.

Preferably, the image display apparatus according to the present invention comprises spatial frequency accentuation means for carrying out spatial frequency accentuation processing on the images, and the display control means controls the display means to display the images subjected to the spatial frequency accentuation processing.

15        to the present invention comprises spatial frequency  
accentuation means for carrying out spatial frequency  
accentuation processing on the images, and the display  
control means controls the display means to display the  
images subjected to the spatial frequency accentuation  
20        processing.

More preferably, the image display apparatus according to the present invention comprises spatial frequency intensity setting means for setting a spatial frequency intensity of the spatial frequency accentuation processing in accordance with operational input from the observer, and the spatial frequency accentuation means carries out the spatial frequency

25        accentuation processing in accordance with operational  
input from the observer, and the spatial frequency  
accentuation means carries out the spatial frequency

09923199 080601

accentuation processing on the images at the set spatial frequency intensity.

In another preferred embodiment, the display means has a color display function, and the display control  
5 means controls the display means to display the two images while changing colors of the two images independently.

In a further preferred embodiment, the display control means controls the display means to display the  
10 two images while making one of the two images flash.

The flashing interval at which the one of the two images is made to flash is variable.

In a still further preferred embodiment, the display means has a display screen, and wherein the  
15 display control means controls the display means to carry out rotating, magnifying and shifting at least one of the two images on the display screen of the display means.

In an advantageous embodiment, the image display  
20 apparatus according to the present invention comprises at least two single image display means for displaying each of the two images singly, and the display control means controls the single image display means to display each of the two images singly.

25 Advantageously, when the mark is displayed in the position designated by the position designation means on the display screen of the display means, the display

109923199-080601  
T09080-66T2660

control means controls the single image display means to also display the mark in a position corresponding to the designated position on the display screen of each of the at least two single image display means.

5 More advantageously, the image display apparatus according to the present invention comprises storage means for separately storing each of the two images along with position information indicating the corresponding position of the mark.

10 To attain the above object, the present invention also provides an image display method of displaying two images of the same subject obtained at different times on display means in a manner such that an observer can fuse the two images together for stereoscopic viewing,  
15 the method comprising the steps of inputting the two images, and controlling the display means to display the two inputted images such that the two inputted images are projected separately into left and right eyes of the observer, whereby the observer can fuse the  
20 images together.

To attain the above object, the present invention further provides a storage medium storing, so as to be readable by an information processing apparatus, a program for constructing an image display system for  
25 displaying two images of the same subject obtained at different times on display means in a manner such that an observer can fuse the two images together for

09923199 "080601

stereoscopic viewing, the program comprising an input module for inputting the two images, and a display control module for controlling the display means to display the two inputted images such that the two  
5 inputted images are projected separately into left and right eyes of the observer, whereby the observer can fuse the images together.

To attain the above object, the present invention also provides an image display apparatus comprising  
10 storage means for storing a plurality of images of the same subject along with information relating to a correspondence relationship between the images and times when the images were taken, searching means for searching for images having a correspondence  
15 relationship therebetween from the plurality of images stored in the storage means, display means for displaying two of the images in a manner enabling an observer to fuse the two images together for stereoscopic viewing, and display control means for  
20 reading any two of the images from the storage means and controlling the display means to display the read two images.

Preferably, the display control means includes image processing means for carrying out different image  
25 processing on each of the two images displayed on the display means.

For example, the image processing means carries

09923199-090601



out processing to make the two images different in color.

Alternatively, the image processing means carries out processing to make one of the two images flash.

5 Preferably, the display control means causes search results from the searching means to be displayed as a list of reduced images, and controls the display means to stereoscopically display two images selected from the displayed list.

10 To attain the above object, the present invention further provides an image display method comprising a storage step of storing a plurality of images of the same subject along with information relating to a correspondence relationship between the images and  
15 times when the images were taken, a searching step of searching for images having a correspondence relationship therebetween from the stored images, a first display step of displaying results of the search, and a second display step of displaying any two images  
20 selected from the search results so as to be viewable as a stereoscopic image.

The above and other objects, features and advantages of the invention will become more apparent from the following detailed description taken in  
25 conjunction with the accompanying drawings.

00023199-080601

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram showing the constitution of an image display apparatus according to a first  
5 embodiment of the present invention;

FIG. 2 shows an example of images displayed on a stereo display device 12 of the image display apparatus shown in FIG. 1 under standard operation;

FIGS. 3A to 3D show examples of images displayed  
10 on the stereo display device 12 of the image display apparatus shown in FIG. 1 after carrying out rotation processing of two images, rotation processing of one image, shifting processing, and magnification processing, respectively;

15 FIG. 4 shows an example of images displayed on a stereo display device of an image display apparatus according to a second embodiment of the present invention;

FIG. 5 shows an example of images displayed on a  
20 stereo display device of an image display apparatus according to a third embodiment of the present invention;

FIG. 6 is a block diagram showing the constitution of an image display apparatus according to a fourth  
25 embodiment of the present invention;

FIG. 7 shows an example in which images displayed on the stereo display device 12 of the image display

09923199-030601

FIG. 8 is a block diagram showing the constitution of an image display apparatus according to a fifth embodiment of the present invention;

FIG. 10 shows another example of images viewed using the crossover method;

FIG. 12 shows an example in which chest X-ray radiographs are displayed rotated through 90 degrees;

FIG. 14 shows an example in which indicator marks have been put on chest X-ray radiographs displayed rotated through 90 degrees; and

## DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Embodiments of the present invention will now be described with reference to the drawings.

According to the present invention, two images of the same subject obtained at different times are inputted, and display means is controlled to display the two images such that the two inputted images are projected separately into the left and right eyes of an observer. As a result, the two images displayed on the display means are fused together by the observer to be viewed stereoscopically by the observer.

When looking for differences between two images of the same subject, a technique is generally used in which the two images are placed, for example, side by side, and are viewed stereoscopically with the naked eyes using the so-called crossover method or the so-called parallel method. In this technique, the two images are fused together by the observer and perceived as a single image. Fusion is difficult to achieve in places where the images differ from one another, giving the observer a feeling of incongruity. It is this feeling of incongruity that allows the observer to find discrepancies between the two images.

The basis of determining a 3-dimensional structure  
25 using both eyes is fusion of the images captured by  
either eye. When viewing the same subject with both  
eyes, the image captured by the left eye and the image

5 varying according to the 3-dimensional structure of the  
subject. That is, the images seen by the left and  
right eyes are almost the same, but there are  
differences in the positions of the image segments  
thereof. A human fuses the two images together and  
10 perceives them as a single image, and moreover judges  
intuitively (i.e. through his/her advanced processing  
ability) 3-dimensional position (i.e. depth) from  
differences in position of the same-shaped object  
between the left eye image and the right eye image.

20 brain.

For example, when the images shown in FIG. 9 are viewed using the crossover method, the image on the left is seen by the right eye and the image on the right by the left eye. If the points ● above the images are perceived as overlapping at the central point ○ in the fused image created in the observer's brain, then the observer should perceive the square

having A written therein (hereinafter referred to as the "A square") as jumping out at him/her and the square having B written therein (hereinafter referred to as the "B square") as being positioned further back.

5           The A square and the B square are actually shifted sideways to different positions in the two images relative to the large enclosing square frame. However, a human fuses the two images into one, and intuitively judges the A square in each of the images to be the  
10       same object and the B square in each of the images to be the same object.

          In the case of the two images shown in FIG. 10, however, the orientations of the letters A and B differ between the two images. The human observer tries to  
15       fuse the two images but can only do so to a limited extent, and thus experiences a strong feeling of incongruity.

          Moving on, a description will now be given of the case of two chest X-ray images taken of the same  
20       subject at different times, with reference to FIGS. 11 and 12. FIG. 11 is a schematic view of X-ray radiography of the chest of a human, and FIG. 12 shows an example in which chest X-ray radiographs are displayed rotated through 90 degrees. As shown in FIG.  
25       11, the chest X-ray radiography equipment is constituted such that an X-ray source is positioned in position A or B, X-rays are radiated out towards a

09023199-080601

5

10

15

25

5

10

20



respectively to the left and right eyes, and spectacles are used in which the left and right eyes are alternately covered using liquid crystals in synchronization with the alternating display; a method  
5 in which left and right images having different directions of polarization are presented simultaneously, and spectacles are used in which the lenses for the left and right eyes are polarized correspondingly; a lenticular display method in which the left and right  
10 images are finely divided into sections and interlaced, and then the sections of the left image are displayed with one directionality and the sections of the right image with another directionality, thus allowing stereoscopic vision without the use of spectacles; and  
15 a method in which the left and right images are presented separately to the left and right eyes using a head-mounted display.

Moreover, in the present invention, to further accentuate the differences between the left and right  
20 images, the colors of the left and right images, i.e. the past and current images, may be changed. X-ray image data is data purely on the intensity of the X-rays, with there being no data relating to color. The images are usually displayed in monochrome, but it is  
25 possible, for example, to present a monochrome image having a blue hue to the left eye and a monochrome image having a red hue to the right eye. When the

09923199 "080601  
T09080" 66T32660

observer fuses the two images, places where the images differ from one another give the observer a feeling of incongruity, which is intensified by the color difference.

5           Moreover, in the present invention, it is also possible to make one of the images flash on and off when displaying the left and right images. As a result, the observer must carry out image fusion repeatedly, which causes the differences between the images to be  
10       seen more clearly.

          Moreover, in the present invention, the observer can designate a position on the display screen upon which the two images are displayed, whereupon an indicator mark is displayed in the designated position.  
15       Examples in which such indicator marks are displayed will now be described with reference to FIG. 13 and FIG. 14.

          FIG. 13 shows an example in which indicator marks have been put on a display screen that displays two  
20       images. FIG. 14 shows an example in which indicator marks have been put on chest X-ray images displayed rotated through 90 degrees.

          Specifically, as shown in FIG. 13, indicator marks M (+) can be put on the display screen displaying the  
25       two images in accordance with operational input from the observer. By looking at the position of the marks M (+) put on the two displayed images, the observer can

09923199-080601

more easily recognize places where the images differ from one another and confirm the differences. Moreover, as shown in FIG. 14, when viewing two chest X-ray images (past and current images) rotated through 90  
5 degrees, marks M (+) can similarly be put on the chest X-ray images in the position of an object P in the chest, allowing changes in the shape of the object P to be recognized more easily.

Moreover, according to the present invention, at  
10 least two further display means for displaying the two images (past and current images) singly are provided, and the two images are displayed on the respective display means. When an indicator mark is put onto the display means displaying the two images together as  
15 described above, the mark is also put onto each of the past image and the current image displayed singly. If necessary, the past and current images thus marked can be stored and then viewed again later, when the marks will be of assistance to the observer.

20 Moreover, in the present invention, the displayed chest X-ray images may be subjected to spatial frequency accentuation processing to accentuate places where there are tumors or the like. The strength of the spatial frequency accentuation processing can be  
25 changed by the observer through operational input.

As described above, according to the present invention, two-eyed stereoscopic viewing of two images

09923199 "080601

of the same subject taken at different times allows places where the images differ from one another to be seen clearly. If the present invention is applied to medical images such as chest X-ray images, CT (computed tomography) images, MRI (magnetic resonance imaging) images or ultrasound diagnosis images, then the differences between two medical images of the same subject taken at different times can be seen. It should be noted, however, that differences seen between the two medical images may not necessarily be indicative of disease. Rather, the present invention has the effect of allowing one to find out whether or not there are sites where changes have occurred between images, possibly due to disease, and the positions of such sites; this information can be used as supplementary information when making medical diagnoses.

#### First embodiment

A description will now be given of a first embodiment of the present invention with reference to the drawings. FIG. 1 is a block diagram showing the constitution of an image display apparatus according to the first embodiment. In this embodiment, a description will be given of an image display apparatus for displaying medical images such as chest X-ray images, CT images, MRI images or ultrasound diagnosis images.

09923199-080601

5 (network I/F) 10 for inputting medical images  
(including a past image and a current image) and  
information relating to the patient in question from a  
network 20.

10 connected to the network I/F 10 via the network 20.  
Chest X-ray images taken by the chest X-ray radiography  
device are transferred along with patient information  
and the like from the chest X-ray radiography device to  
the image display apparatus via the network 20.

15       The chest X-ray radiography device may be, for example, a device that converts the X-ray intensity distribution directly into a digital image using a so-called X-ray flat panel sensor, or a device in which the X-ray intensity distribution is recorded on an X-ray film. The chest X-ray images inputted via the network 20 may be, for example, digital images obtained by scanning a photostimulable fluorescent body called an imaging plate, digital images obtained from a device comprised of a photomultiplier tube and a television camera, or digital images obtained from an X-ray film using a film scanner.

Medical images inputted via the network I/F 10 are

5 that the images are of the same subject and indicating  
the times when the images were taken. As a result, it  
is clear that the images correspond to one another, and  
the amount of time elapsed between the images is known.  
The storage device 9 is comprised of a hard disk or the  
like. Desired medical images can be read from the  
storage device 9, with the reading being controlled by  
the control means 1.

When, for example, a past chest X-ray image and the corresponding current chest X-ray image of the same subject are read from the storage device 9, the past chest X-ray image is temporarily stored in a VRAM 7 and then sent via a video interface (video I/F) 8 to a display device 14, which displays the past chest X-ray image; the current chest X-ray image is temporarily stored in a VRAM 5 and then sent via a video interface (video I/F) 6 to a display device 13, which displays the current chest X-ray image.

Moreover, the past chest X-ray image and the current chest X-ray image read from the storage device 25 9 are composited by the control means 1, and the composite image thus obtained is temporarily stored in a VRAM 3 and then sent via a video interface (video

I/F) 4 to a stereo display device 12 such as a lenticular display device.

The composite image is displayed on the stereo display device 12 in such a way that the past chest X-ray image and the current chest X-ray image are presented separately to the right and left eyes respectively of an observer 15.

The control means 1 contains a CPU, a ROM, a RAM, a chip set and so on. The CPU carries out overall control of the image display apparatus in accordance with a program stored in the ROM, and also carries out processing such as that for forming the composite image described above. An operation panel 11 that can be operated by the observer 15 is used for inputting commands to the control means 1, for setting modes, and so on.

Various keys for inputting commands, setting modes and so on are provided on the operation panel 11. When a key is pressed, corresponding key information is inputted into the control means 1 via an operation panel interface 2.

When the observer 15 wishes to view the chest X-ray images of a certain patient, the observer 15 carries out operations through the operation panel 11 for reading the corresponding image data from the storage device 9. Here, it shall be assumed that, in accordance with these operations, a past chest X-ray

09923159 080601

image and a corresponding current chest X-ray image of the same patient are read from the storage device 9, and the two images are composited as described above.

It should, however, be noted that a command for  
5 reading the past chest X-ray image, a command for reading the current chest X-ray image, and a command for compositing the two images can also each be sent separately by operating the operation panel 11 accordingly.

10 When the past and current chest X-ray images of the same patient are read in, the past chest X-ray image is displayed on the display device 14 and the current chest X-ray image on the display device 13. Moreover, a composite image as described above is  
15 displayed on the stereo display device 12 in such a way that the past chest X-ray image and the current chest X-ray image are presented separately to the right eye and the left eye respectively of the observer 15. As a result, the observer 15 can fuse the presented images  
20 together, perceiving them as a single stereoscopic image. The observer 15 compares the images displayed on the display devices 12, 13 and 14 and looks for changes indicative of disease in the patient in question.

25 Depending on whether or not the image displayed on the stereo display device 12 can be seen stereoscopically by the observer 15, the displayed

09923199-080601



image can either be left as it is or can be rotated through, for example, 90 degrees using rotation processing. The choice of whether to rotate or not can be carried out by operational input from the operation panel 11. Moreover, rotation processing for rotating by any chosen angle can be carried out, with it being possible to set the angle of rotation from the operation panel 11.

Furthermore, in addition to the rotation processing described above, other processing is also possible, such as rotation processing in which only one of the left eye image and the right eye image is rotated, shifting processing in which one of the left eye image and the right eye image is shifted in the vertical direction, and magnification processing in which one of the left eye image and the right eye image is enlarged or reduced in size. These types of processing are carried out by the control means 1. Specifically, processing such as image magnification, shifting and rotation can be carried out by the control means 1 controlling the addresses and rate of reading from the VRAM 3. As a result, the left and right eye images can be manipulated until a stereoscopically viewable fused image is obtained.

If, in viewing the images displayed on the stereo display device 12, the observer 15 intuitively perceives any places that cannot be viewed

09923199-080601

5 (the past chest X-ray image).

FIG. 2 shows an example of images displayed on the stereo display device 12 of the image display apparatus shown in FIG. 1 under standard operation (i.e. with no rotation processing, shifting processing or magnification processing), while FIGS. 3A to 3D show examples of images displayed on the stereo display device 12 of the image display apparatus shown in FIG. 1 after carrying out rotation processing of two images, rotation processing of one image, shifting processing, and magnification processing, as described above, respectively.

Under standard operation, the image captured by  
25 the right eye is displayed on the left side and the  
image captured by the left eye on the right side of the  
stereo display device 12, as shown in FIG. 2. That is,

The observer 15 operates the operation panel 11 while viewing the displayed images. By operating the operation panel 11, simple image processing can be carried out interactively to make any differences between the two images (the past and current chest X-ray images) easily visible; for example, both images can be rotated as shown in FIG. 3A, one of the images can be rotated as shown in FIG. 3B, the position of one of the images can be corrected by shifting vertically as shown in FIG. 3C, or one of the images can be enlarged or reduced in size as shown in FIG. 3D.

20           It is possible to not only carry out processing  
relating to the positions, orientations and sizes of  
the left and right images, but, again using the control  
means 1, also to change the display brightness and the  
like of the two images independently. Moreover, in  
25 terms of the technical concept of the present invention,  
it is also possible to implement more advanced image  
processing in which an image segment is designated and

warping is carried out on the designated image segment.

The reason that such rotation, shifting, magnification and brightness adjustment are necessary is that the position of the patient's body during the X-ray radiography and the radiographic conditions may be different for each of the X-ray images. For example, if the past image is an analog image that was taken using an old-style film screen system and then digitized by scanning the film using a film scanner, then the size of the image may well be different to that of the current image.

As described above, according to the present embodiment, subtle differences between two images of the same subject obtained at different times can be clearly shown to the observer without carrying out complex image processing.

It should also be noted that, although in the present embodiment a stereo display device such as a lenticular display device that can be viewed without spectacles was used, the present invention is not limited to such a display device. Any display device that projects separate images to the left and right eyes of the observer and thus allows stereoscopic viewing may be used, for example a time division type display device that uses liquid crystal shutter spectacles, a display device that uses polarizing spectacles, or a display device that uses a head-

09923199 080601

mounted display.

09923199 080601

A description will now be given, with reference to FIGS. 15A to 15D, of an example of a series of operations carried out by the observer 15 using the operation panel 11 to display chest X-ray images or the like on the display devices 12, 13 and 14. The observer 15 first uses the operation panel 11 to send a search command, whereupon the control means 1 switches the display on, for example, the display device 13 or the display device 14 over to a search screen, as shown in FIG. 15A. The observer 15 now uses the operation panel 11 to input a patient's name or code onto the search screen, whereupon the control means 1 reads images such as chest X-ray images corresponding to the inputted name or code from the storage device 9, and displays the read images as a list of images or a list of reduced images or the like along with the date when each image was taken and other related medical information, as shown in FIG. 15B. The observer 15 uses a mouse or the like to move a pointer P over the display screen shown in FIG. 15B and select desired images, whereupon the selected images are displayed on the display devices 13 and 14, as shown in FIGS. 15C and 15D. A composite image formed from the two selected images as described earlier is also displayed on the stereo display device 12.

As a result of the above, the two images taken at

5

A description will now be given of a second embodiment of the present invention with reference to FIG. 4. FIG. 4 shows an example of images displayed on a stereo display device of an image display apparatus according to the second embodiment. In FIG. 4, the image captured by the right eye is shown on the left side and the image captured by the left eye on the right side. The image display apparatus has the same constitution in the present embodiment as in the first embodiment described above, and hence the description of this constitution will be omitted here.

20

25

When the two images having different colors are viewed stereoscopically by the observer 15, a stronger feeling of incongruity is sensed in places where the images differ from one another (i.e. places where it is difficult to achieve stereoscopic vision) than in the first embodiment, in which only the images themselves differed but the colors were the same. Differences between the two images are thus more easily perceived than in the first embodiment.

10 In actual practice, it may be difficult for the observer 15 to fuse the left and right eye images together if the colors of the two images are different from the start. In such a case, the left and right eye images are first both displayed in black and white, and  
15 the observer 15 then carries out rotation, shifting, magnification and so on as described above in the first embodiment until the two images can be fused together into a single stereoscopic image. Once fusion has been achieved, the observer 15 then gradually changes the  
20 colors of the two images, for example making the current image blue and the past image red, while continuing to view the fused image. As a result, the fused state that was obtained while viewing in black and white is maintained. Once the displayed images  
25 have become completely red and blue respectively, the observer 15 makes observations and a diagnosis.

09923199 080601

A description will now be given of a third embodiment of the present invention with reference to FIG. 5. FIG. 5 shows an example of images displayed on a stereo display device of an image display apparatus according to the third embodiment. In FIG. 5, the image captured by the right eye is shown on the left side and the image captured by the left eye on the right side. The image display apparatus has the same constitution in the present embodiment as in the first embodiment described above, and hence the description of this constitution is omitted here.

The present embodiment differs from the first or second embodiment in that there is a function for making either the left eye image or the right eye image flash on and off. For example, in FIG. 5, the left eye image can be made to flash. The rate of flashing can be freely changed by the observer 15.

This flashing is effective particularly when the colors of the two images are changed as in the second embodiment. If one of the images is made to flash relatively slowly (for example at about 1 second intervals); then places where the images differ from one another are seen by the observer 15 as an after-  
image, and hence it becomes easier to notice such places.

It is also effective, for example, to alternate



the left eye image with the right eye image rather than making the left eye image flash on and off.

In the present embodiment, the left eye image was made to flash, but it goes without saying that the same  
5 effect is achieved if the right eye image is made to flash instead.

The processing for making one of the images flash or changing the colors of the images can be carried out by the control means 1 using known methods.

10

#### Fourth embodiment

A description will now be given of a fourth embodiment of the present invention with reference to FIGS. 6 and 7. FIG. 6 is a block diagram showing the  
15 constitution of an image display apparatus according to the fourth embodiment. FIG. 7 shows an example in which images displayed by the stereo display device 12 of the image display apparatus shown in FIG. 6 have been subjected to marking.

20 In FIG. 6, blocks having the same functions as in the first embodiment are designated by the same reference numerals as in the first embodiment; the description of these blocks will either be abbreviated or omitted altogether here.

25 In contrast with the first embodiment, in the present embodiment there is a mouse 16 for designating a position on the display screen of the stereo display

D9923199-080601

5  
10

15  
20  
25

5

10

## 15

20

25

processing and then display the chest X-ray images thus processed on the stereo display device 12.

Moreover, it is possible for the spatial frequency intensity of the spatial frequency accentuation processing to which the chest X-ray images are subjected to be changed in accordance with operational input from the observer 15.

A method of accentuating an image by frequency is called unsharp masking. In this method, representing the initially obtained image by G and the image after subjecting to unsharp processing (blurring) by Gu, a new processed image Gm is produced in accordance with the following formula (1) using an accentuation degree coefficient a.

$$G_m = G + a \cdot (G - G_u) \quad (1)$$

The accentuation degree coefficient a is a positive variable. The larger the value, the more the high spatial frequency domain is accentuated. A common method of creating Gu is to use for each targeted pixel the mean value of the pixels in a region surrounding that targeted pixel. The spatial frequency domain that is accentuated is determined by the size of this surrounding region.

Referring to FIG. 8, in the present embodiment, unsharp processing as described above is carried out by the control means 1, and a VRAM 17 and a VRAM 18 are provided for storing the unsharp images computed for

10923169-080601

5

10

25

presented to the observer at the same time, further improving the probability of changes indicative of disease being detected.

Moreover, in the embodiments described above, examples have been given in which the present invention is applied to medical images such as chest X-ray images. However, the present invention is not limited to medical images, but rather can be applied to the intuitive detection of differences between any two images.

Furthermore, the present invention can either be realized using dedicated display devices or using a personal computer, a workstation or the like.

Furthermore, in the embodiments described above, the display processing in the image display apparatus is carried out in accordance with a program stored in a ROM of the control means 1, but the program may instead be supplied stored on a storage medium such as a ROM, a DVD-ROM, a CD-ROM or a memory card. In such a case, a CPU reads the program from the storage medium and executes the program to achieve the purposes of the present invention. The storage medium on which the program is stored thus constitutes the present invention.

According to the embodiments of the present invention described above, display means is controlled to display the two images such that two images of the

09923199-080601

same subject obtained at different times are projected separately to the left and right eyes of an observer. As a result, subtle differences between the two images of the same subject obtained at different times can be  
5 clearly shown to the observer without carrying out complex image processing.

Moreover, by marking places where a feeling of incongruity is sensed, places where the two images differ from one another can be shown more clearly.

10 Furthermore, by subjecting chest X-ray images to spatial frequency accentuation processing and then displaying the chest X-ray images thus processed on the display means, places where changes indicative of disease have occurred are accentuated, and the chest X-  
15 ray images can be viewed stereoscopically with improved sharpness, thus allowing places where the images differ from one another to be identified more clearly.

Furthermore, if the colors of the two images are changed independently while displaying the two images  
20 on the display means, then a stronger feeling of incongruity is sensed in places where the two images differ from one another, and hence it becomes easier to perceive differences between the two images

Furthermore, if one of the two images is made to  
25 flash while displaying the two images on the display means, then places where the images differ from one another are seen by the observer as an after-image, and

09923199-080601  
T09080-66TE660

hence it becomes easier to notice such places.

Furthermore, if processing is carried out in which at least one of the two images displayed on the display means is rotated, magnified or shifted on the display screen of the display means (possibly while also independently changing the colors of the two images or making one of the two images flash as described above), then the observer can obtain a clearer stereoscopic image.

10 Furthermore, if the two images are marked as described above and then stored separately along with position information indicating the position of the mark, then when the images are subsequently retrieved and viewed once again, the marks will be of assistance  
15 to the observer.

09923199-080601